

View Online at <https://aerobasegroup.com/nsn/5930-01-263-5034>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

4.718 inches

Overall Height:

1.200 inches

Overall Width:

0.960 inches

Body Width:

0.850 inches

Body Height:

1.200 inches

Case Material:

Metal

Actuator Length:

Between 1.020 inches and 1.035 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.164 inches and 0.210 inches

Actuator Width:

Between 0.723 inches and 0.740 inches

Actuator Color:

Red single actuator and green single actuator

Illuminated Actuator Color:

Red single actuator and green single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

1.578 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

Terminal Type And Quantity:

5 tab, solder lug and 12 turret

Specification Data:

81349-mil-s-22885/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0