

View Online at <https://aerobasegroup.com/nsn/5930-01-263-5036>

**Body Style:**

Panel mounted

**Overall Length:**

3.250 inches

**Overall Height:**

1.200 inches

**Overall Width:**

0.960 inches

**Body Width:**

0.850 inches

**Body Height:**

1.200 inches

**Actuator Length:**

1.040 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.140 inches

**Actuator Width:**

0.800 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

White single actuator and green single actuator

**Illuminated Actuator Color Sequence:**

Upper half of actuator white, lower half of actuator green

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

3.110 inches

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

4 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

5 tab solder lug and 12 turret

**Specification Data:**

81349-mil-s-22885/9 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0