NSN 5930-01-263-5047

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-263-5047

- **Body Style:**
- Panel mount
- **Overall Length:**
- 1.200 inches
- **Overall Height:**
- 2.828 inches
- **Overall Width:**
- 0.960 inches
- **Body Length:**
- 1.090 inches
- **Body Width:**
- 0.850 inches
- **Body Height:**
- 2.478 inches
- Actuator Length:

1.040 inches

Actuator Style:

Rectangular

- **Actuator Width:**
- 0.800 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Green single actuator and amber single actuator

Illuminated Actuator Color Sequence:

Top half of actuator green bottom half of actuator amber

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

toh

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Special Features:

Horizontally split screen; actuator flush

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity: colder lug and 6 turret

NSN 5930-01-263-5047

Push Switch - Page 2 of 2



Specification Data:

81349-mil-s-22885/9 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0