## NSN 5930-01-263-5052

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-263-5052
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Shock resistant
Overall Length:
4.718 inches
Overall Height:
1.200 inches
Overall Width:
0.960 inches
Body Width:
0.960 inches
Body Height:
1.200 inches
Case Material:
Metal
Actuator Length:
Between 1.020 inches and 1.035 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.164 inches and 0.210 inches
Actuator Width:
Between 0.723 inches and 0.740 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Blue single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
4.578 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes
inductive ac and 1.500 amperes lamp ac

**Test Data Document:** 

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

## NSN 5930-01-263-5052

Push Switch - Page 2 of 2



Terminal	<b>Type</b>	And	Quantity	y:
----------	-------------	-----	----------	----

6 turret and 5 tab, solder lug

**Specification Data:** 

81349-mil-s-22885/9 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0