# NSN 5930-01-263-5937

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-263-5937

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.440 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.920 inches
Actuator Style:
Rectangular
Actuator Height:
0.290 inches
Actuator Width:
0.920 inches
Actuator Color:
Black single actuator and black single actuator
Illuminated Actuator Color:
Amber single actuator and amber single actuator
Actuator Inscription:
Pump stop single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
33.150 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and horizontal split lens
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit

## NSN 5930-01-263-5937

Push Switch - Page 2 of 2



### **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

### **Special Features:**

Lower half of lens engraved with grid pattern 0.440 in. Lg by 0.120 in. W

**Precious Material And Location:** 

Contacts silver

#### **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0