NSN 5930-01-263-5937

Push Switch - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5930-01-263-5937

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.440 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Case Material:

Metal

Actuator Length:

0.920 inches

0.020 1101100

Actuator Style:

Rectangular

Actuator Height:

0.290 inches

Actuator Width:

0.920 inches

Actuator Color:

Black single actuator and black single actuator

Illuminated Actuator Color:

Amber single actuator and amber single actuator

Actuator Inscription:

Pump stop single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

33.150 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and horizontal split lens

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-263-5937

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

inductive ac and 1.000 amperes lamp ac

Special Features:

Lower half of lens engraved with grid pattern 0.440 in. Lg by 0.120 in. W

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0