

View Online at <https://aerobasegroup.com/nsn/5930-01-263-5939>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Explosion proof and humidity resistant

**Overall Length:**

3.440 inches

**Overall Height:**

1.000 inches

**Overall Width:**

1.000 inches

**Body Width:**

0.750 inches

**Body Height:**

0.750 inches

**Case Material:**

Metal

**Actuator Length:**

0.920 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.290 inches

**Actuator Width:**

0.920 inches

**Actuator Color:**

Black single actuator and black single actuator

**Illuminated Actuator Color:**

Amber single actuator and amber single actuator

**Actuator Inscription:**

Hud down single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Mounting Surface To Terminal End Distance:**

3.150 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Actuator seal and horizontal split lens

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

**Special Features:**

Lower half of lens engraved with grid pattern 0.440 in. Lg by 0.120 in. W

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

1 socket, integrated wire termination

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0