

View Online at <https://aerobasegroup.com/nsn/5930-01-263-5939>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.440 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Case Material:

Metal

Actuator Length:

0.920 inches

Actuator Style:

Rectangular

Actuator Height:

0.290 inches

Actuator Width:

0.920 inches

Actuator Color:

Black single actuator and black single actuator

Illuminated Actuator Color:

Amber single actuator and amber single actuator

Actuator Inscription:

Hud down single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

3.150 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and horizontal split lens

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Special Features:

Lower half of lens engraved with grid pattern 0.440 in. Lg by 0.120 in. W

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0