

View Online at <https://aerobasegroup.com/nsn/5930-01-263-6848>

Overall Length:

2.450 inches

Body Diameter:

1.077 inches

Unthreaded Mounting Hole Diameter:

Between 0.213 inches and 0.223 inches

Longest Horizontal Distance Between Mounting Centers:

0.830 inches

Longest Vertical Distance Between Mounting Centers:

0.972 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -20.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

6000.00 pounds per square inch gage

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

10000.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

10.0 milliamperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

2700.00 actuation point pounds per square inch gage and 3200.00 actuation point pounds per square inch gage and 2300.00 deactuation point pounds per square inch gage and 2700.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

5.0 dc at sea level single voltage

Media For Which Designed:

Liquid

Specification Data:

81873-84000477 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0