NSN 5930-01-263-9301

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5930-01-263-9301

view Online at https://defobasegroup.com/nsn/0330-01-203-3001
Body Style:
Panel mounted
Overall Length:
3.319 inches
Overall Height:
1.355 inches
Overall Width:
0.845 inches
Body Width:
1.355 inches
Body Height:
2.812 inches
Actuator Length:
1.100 inches
Actuator Style:
Rectangular
Actuator Height:
0.225 inches
Actuator Width:
0.845 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.094 inches
Inclosure Type:
Uninclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes
inductive ac and 1.500 amperes lamp ac
Special Features:
Horizonal split lens diffuser

Terminal Type And Quantity:

6 tob solder lug and 6 turret

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5930-01-263-9301

Push Switch - Page 2 of 2



Specification Data	Spe	ecifica	ition	Data:
--------------------	-----	---------	-------	-------

81349-mil-s-22885/15 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0