# NSN 5930-01-263-9601

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-263-9601

# Body Style:

Hole mounted

## Hazardous Locations/environmental Protection:

Dustproof

# Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

#### **Overall Height:**

0.870 inches

#### **Overall Width:**

0.380 inches

#### **Body Length:**

0.510 inches

#### Body Width:

0.210 inches

## **Body Height:**

0.350 inches

# Unthreaded Mounting Hole Diameter:

0.088 inches

## Actuator Style:

Leaf

## Actuator Width:

0.380 inches

## **Actuator Free Position Height:**

0.450 inches

#### Maximum Voltage Rating In Volts:

125.0 ac and 30.0 dc

#### **End Application:**

5815-01-062-8194 terminal, communications

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Actuating Force:

5.0 ounces

#### **Actuator Movement:**

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.002 differential inches

# Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 1.000 amperes resistive ac

# Terminal Type And Quantity:

3 turret

# NSN 5930-01-263-9601

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

