

View Online at <https://aerobasegroup.com/nsn/5930-01-264-1728>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Height:**

2.600 inches

**Bushing Length:**

1.000 inches

**Body Length:**

1.060 inches

**Body Width:**

Between 0.875 inches and 0.937 inches

**Body Height:**

Between 0.469 inches and 0.531 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.237 inches and 0.247 inches

**Actuator Height:**

0.540 inches

**Actuator Free Position Height:**

1.540 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

16.0 ounces

**Switch Actuating Force:**

Between 32.0 ounces and 160.0 ounces

**Actuator Movement:**

Between 0.010 pretravel inches and 0.020 pretravel inches and 0.550 overtravel inches and 0.015 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes lamp dc

**Special Features:**

Termination on right side of body

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0