

View Online at <https://aerobasegroup.com/nsn/5930-01-264-1728>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Height:

2.600 inches

Bushing Length:

1.000 inches

Body Length:

1.060 inches

Body Width:

Between 0.875 inches and 0.937 inches

Body Height:

Between 0.469 inches and 0.531 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.247 inches

Actuator Height:

0.540 inches

Actuator Free Position Height:

1.540 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

16.0 ounces

Switch Actuating Force:

Between 32.0 ounces and 160.0 ounces

Actuator Movement:

Between 0.010 pretravel inches and 0.020 pretravel inches and 0.550 overtravel inches and 0.015 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes lamp dc

Special Features:

Termination on right side of body

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0