# NSN 5930-01-264-2886

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-264-2886

Hole mounted

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

Body Length:

0.510 inches

#### **Body Width:**

0.200 inches

#### **Body Height:**

0.350 inches

#### **Unthreaded Mounting Hole Diameter:**

0.088 inches

#### **Actuator Style:**

Round

#### Actuator Diameter:

#### 0.060 inches

#### Actuator Height:

0.050 inches

#### **Actuator Free Position Height:**

0.050 inches

### Maximum Voltage Rating In Volts:

28.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

#### Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

#### Switch Release Force:

1.0 ounces

#### Switch Actuating Force:

5.0 ounces

#### **Actuator Movement:**

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

#### Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc

#### **Special Features:**

Includes 25.000 in. Piece of black flex tubing

## Terminal Type And Quantity:

2 wire lead

### Shelf Life:

N/a

# NSN 5930-01-264-2886

Sensitive Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

