

View Online at <https://aerobasegroup.com/nsn/5930-01-264-2886>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

Body Length:

0.510 inches

Body Width:

0.200 inches

Body Height:

0.350 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.060 inches

Actuator Height:

0.050 inches

Actuator Free Position Height:

0.050 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc

Special Features:

Includes 25.000 in. Piece of black flex tubing

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0