

View Online at <https://aerobasegroup.com/nsn/5930-01-264-2892>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Waterproof

**Overall Length:**

2.043 inches

**Overall Height:**

0.640 inches

**Overall Width:**

0.640 inches

**Body Diameter:**

0.562 inches

**Bushing Length:**

0.425 inches

**Body Length:**

1.020 inches

**Actuator Diameter:**

0.500 inches

**Actuator Height:**

0.620 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Blue single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Facsimile set an/uxc-4

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 1.000 amperes resistive ac

**Precious Material And Location:**

Contacts gold

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 turret and 2 tab, solder lug

**Specification Data:**

81349-mil-s-22885/79 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0