

View Online at <https://aerobasegroup.com/nsn/5930-01-264-2892>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

2.043 inches

Overall Height:

0.640 inches

Overall Width:

0.640 inches

Body Diameter:

0.562 inches

Bushing Length:

0.425 inches

Body Length:

1.020 inches

Actuator Diameter:

0.500 inches

Actuator Height:

0.620 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Blue single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Facsimile set an/uxc-4

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 1.000 amperes resistive ac

Precious Material And Location:

Contacts gold

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 turret and 2 tab, solder lug

Specification Data:

81349-mil-s-22885/79 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A053a0