NSN 5930-01-264-5120

Thermostatic Switch - Page 1 of 2

Shelf Life:

N/a



View Online at https://aerobasegroup.com/nsn/5930-01-264-5120

Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
0.344 inches
Overall Height:
0.080 inches
Body Diameter:
0.263 inches
End Application:
1430-01-087-6338 transformer, power
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Surface
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Wire lead
Contact Load Current Rating:
500.0 milliamperes resistive load second voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
210.00 actuation point degrees fahrenheit and 180.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Frequency In Hertz:
60.0 first voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Disc
Test Data Document:
81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-s-24236/13 government specification

NSN 5930-01-264-5120

Thermostatic Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A048b0