NSN 5930-01-264-8924

Slide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-264-8924
Body Style:
Printed circuit
Overall Length:
0.780 inches
Overall Height:
0.500 inches
Overall Width:
Between 0.370 inches and 0.405 inches
Body Length:
0.780 inches
Body Width:
Between 0.370 inches and 0.405 inches
Body Height:
Between 0.230 inches and 0.300 inches
Case Material:
Plastic
Actuator Length:
Between 0.045 inches and 0.065 inches
Actuator Style:
Rectangular
Actuator Height:
0.040 inches
Actuator Width:
Between 0.055 inches and 0.085 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained
Maximum Voltage Rating In Volts:
24.0 dc
Mounting Method:
Printed circuit
Nonpile-up Contact Arrangement:
1 pole, single throw, both positions maintained 7th switch unit
Contact Load Current Rating At Maximum Rated Voltage:
25.000 milliamperes resistive dc
Special Features:
Mtg ears removed
Precious Material And Location:
Contact surfaces gold
Test Data Document:
81349-mil-s-83504 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

14 printed circuit

NSN 5930-01-264-8924

Slide Switch - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-s-83504/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0