

View Online at <https://aerobasegroup.com/nsn/5930-01-264-8924>

Body Style:

Printed circuit

Overall Length:

0.780 inches

Overall Height:

0.500 inches

Overall Width:

Between 0.370 inches and 0.405 inches

Body Length:

0.780 inches

Body Width:

Between 0.370 inches and 0.405 inches

Body Height:

Between 0.230 inches and 0.300 inches

Case Material:

Plastic

Actuator Length:

Between 0.045 inches and 0.065 inches

Actuator Style:

Rectangular

Actuator Height:

0.040 inches

Actuator Width:

Between 0.055 inches and 0.085 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

24.0 dc

Mounting Method:

Printed circuit

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained 7th switch unit

Contact Load Current Rating At Maximum Rated Voltage:

25.000 milliamperes resistive dc

Special Features:

Mtg ears removed

Precious Material And Location:

Contact surfaces gold

Test Data Document:

81349-mil-s-83504 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

14 printed circuit

Specification Data:

81349-mil-s-83504/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0