## NSN 5930-01-264-8925

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-264-8925

- **Body Style:**
- Panel mounted
- **Overall Length:**
- 2.700 inches
- **Overall Height:**
- 0.875 inches
- **Overall Width:**
- 0.875 inches
- **Body Width:**
- 0.750 inches
- **Body Height:**
- 0.750 inches
- Actuator Length:
- 0.700 inches
- Actuator Style:

### Rectangular

- Actuator Height:
- 0.270 inches
- Actuator Width:
- 0.700 inches
- Actuator Color:
- White single actuator
- Illuminated Actuator Color:
- White single actuator
- Maximum Voltage Rating In Volts:
- 115.0 ac and 28.0 dc
- Mounting Surface To Terminal End Distance:
- 2.330 inches
- Inclosure Type:
- Fully enclosed
- **Mounting Method:**
- Panel
- Nonpile-up Contact Arrangement:
- 2 pole, double throw, both positions maintained single switch unit
- Contact Load Current Rating At Maximum Rated Voltage:
- 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac
- **Test Data Document:**
- 81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

5 tab, solder lug and 6 turret

#### Specification Data:

813/10-mil-c-22885/8/ government energification

# NSN 5930-01-264-8925

Push Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

