

View Online at <https://aerobasegroup.com/nsn/5930-01-265-3078>

**Thread Class:**

2b single mounting facility

**Overall Length:**

12.374 inches

**Overall Diameter:**

6.000 inches

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

3.468 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

1.734 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

3.000 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded hole single mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

20 single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

300.0 ac at sea level

**Mounting Facility Pattern:**

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

40.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

100.0 amperes resistive load ac at sea level

**Special Features:**

Panel mtg not to exceed 1.000 in. Thickness

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circular frame

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0