NSN 5930-01-265-3078

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-265-3078

Thread Class:

2b single mounting facility

Overall Length:

12.374 inches

Overall Diameter:

6.000 inches

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

3.468 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.734 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.000 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

20 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

300.0 ac at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

40.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

100.0 amperes resistive load ac at sea level

Special Features:

Panel mtg not to exceed 1.000 in. Thickness

NSN 5930-01-265-3078

Rotary Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Tap, circular frame
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0