## NSN 5930-01-265-3078

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-265-3078

**Thread Class:** 

2b single mounting facility

**Overall Length:** 

12.374 inches

**Overall Diameter:** 

6.000 inches

**Individual Section Quantity:** 

3

**Longest Horizontal Distance Between Mounting Centers:** 

3.468 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:** 

1.734 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:** 

3.000 inches single mounting facility

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Threaded hole single mounting facility

**Features Provided:** 

Actuator knob

Thready Qty Per Inch (tpi):

20 single mounting facility

**Thread Size:** 

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:** 

300.0 ac at sea level

**Mounting Facility Pattern:** 

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes each section rear

**Switch Actuator Positioning Increment:** 

40.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Adjustable stop single actuator

**Contact Load Current Rating:** 

100.0 amperes resistive load ac at sea level

**Special Features:** 

Panel mtg not to exceed 1.000 in. Thickness

## NSN 5930-01-265-3078

Rotary Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Tap, circular frame
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0