NSN 5930-01-265-5502

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-265-5502

Thread Class: 2b single mounting facility **Overall Length:** 5.870 inches **Overall Height:** 2.910 inches **Overall Width:** 2.810 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.000 inches single mounting facility **Shortest Horizontal Distance Between Mounting Centers:** 1.000 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.180 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 500.0 highest ac voltage rating at sea level **Switch Actuator Momentary Position:** Clockwise single actuator **Mounting Facility Pattern:** Isosceles triangle single mounting facility **Switch Actuator Indexing Position Quantity:** 4 single actuator **Terminal Type:** Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

NSN 5930-01-265-5502

Rotary Switch - Page 2 of 2



Precious Material And Location: Contacts and rotor blade surfaces silver Precious Material: Silver Style Designator: Tap, circuit selector Thread Series Designator: Unc single mounting facility Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A052b0