NSN 5930-01-265-7758

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-265-7758

Overall Height:

0.500 inches

Body Height:

Between 0.350 inches and 0.395 inches

Overall Diameter:

Between 0.560 inches and 0.640 inches

Tempurature Sensing Element Type:

Internal sensor

Mounting Method:

Clamp

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Decrease

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

15.00 differential point degrees fahrenheit and 115.00 actuation point degrees fahrenheit and 130.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc

Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-24236/1 government specification

Shelf Life:

N/a

- Unit Of Measure:
- --
- Demilitarization:
- No

NSN 5930-01-265-7758

Thermostatic Switch - Page 2 of 2

Fiig: A048b0

