## NSN 5930-01-265-7773

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-265-7773

Overa	II I	end	ıth:

Between 0.322 inches and 0.366 inches

**Overall Height:** 

Between 0.065 inches and 0.095 inches

**Body Diameter:** 

Between 0.248 inches and 0.278 inches

**Tempurature Sensing Element Type:** 

Internal sensor

**Mounting Method:** 

Clamp

**Features Provided:** 

Hermetically sealed case

**Contact Action Stimulus:** 

Increase

## **Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

## **Terminal Type:**

Wire lead

## **Contact Load Current Rating:**

500.0 milliamperes resistive load second voltage and 500.0 milliamperes inductive load second voltage and 200.0 milliamperes lamp load second voltage

## **Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

## **Contact Stimulus Rating:**

122.00 actuation point degrees fahrenheit and 138.00 actuation point degrees fahrenheit and 92.00 deactuation point degrees fahrenheit and 108.00 deactuation point degrees fahrenheit and 30.00 differential point degrees fahrenheit

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

#### Frequency In Hertz:

60.0 first voltage

## Media For Which Designed:

Gas or liquid

## **Style Designator:**

Disc

## **Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-s-24236/13 government specification

## Shelf Life:

N/a

## **Unit Of Measure:**

\_

Demilitarization:

# NSN 5930-01-265-7773

Thermostatic Switch - Page 2 of 2



Fiig:

A048b0