

View Online at <https://aerobasegroup.com/nsn/5930-01-265-7773>

**Overall Length:**

Between 0.322 inches and 0.366 inches

**Overall Height:**

Between 0.065 inches and 0.095 inches

**Body Diameter:**

Between 0.248 inches and 0.278 inches

**Temperature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Clamp

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

500.0 milliamperes resistive load second voltage and 500.0 milliamperes inductive load second voltage and 200.0 milliamperes lamp load second voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

122.00 actuation point degrees fahrenheit and 138.00 actuation point degrees fahrenheit and 92.00 deactuation point degrees fahrenheit and 108.00 deactuation point degrees fahrenheit and 30.00 differential point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc

**Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-s-24236/13 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

**Fig:**

A048b0