

View Online at <https://aerobasegroup.com/nsn/5930-01-265-7773>

Overall Length:

Between 0.322 inches and 0.366 inches

Overall Height:

Between 0.065 inches and 0.095 inches

Body Diameter:

Between 0.248 inches and 0.278 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Clamp

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

500.0 milliamperes resistive load second voltage and 500.0 milliamperes inductive load second voltage and 200.0 milliamperes lamp load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

122.00 actuation point degrees fahrenheit and 138.00 actuation point degrees fahrenheit and 92.00 deactuation point degrees fahrenheit and 108.00 deactuation point degrees fahrenheit and 30.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc

Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-24236/13 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A048b0