## NSN 5930-01-265-7964

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-265-7964

**Thread Class:** 

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Moisture resistant and explosion proof

**Overall Length:** 

1.697 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.094 inches single actuator

**Shaft Diameter:** 

0.125 inches single actuator

**Shaft Length:** 

0.375 inches single actuator

**Overall Diameter:** 

Between 0.670 inches and 0.800 inches

**Individual Section Quantity:** 

1

**Nonturn Device Type:** 

Flatted bushing at 3: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 single section front

**Throw Quantity:** 

4 single section rear

**Mounting Method:** 

Threaded bushing w/panel seal single mounting facility

**Thread Size:** 

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Rotor Through Connection Quantity:** 

2 single section

**Switch Actuator Indexing Position Quantity:** 

4 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

## NSN 5930-01-265-7964

Rotary Switch - Page 2 of 2

Shelf Life:

**Unit Of Measure:** 

Demilitarization:

N/a

No Fiig: A052b0



Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
500.0 milliamperes resistive load dc at sea level and 250.0 milliamperes inductive load dc at sea level
Style Designator:
Tap, circular, bushing mount
Test Data Document:
81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef single mounting facility
Specification Data:
81349-mil-s-3786/13 government specification