## NSN 5930-01-265-7966

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-265-7966

**Thread Class:** 

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Moisture resistant and explosion proof

**Overall Length:** 

1.965 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.094 inches single actuator

**Shaft Diameter:** 

0.125 inches single actuator

**Shaft Length:** 

0.375 inches single actuator

**Overall Diameter:** 

Between 0.670 inches and 0.800 inches

**Nonturn Device Radius:** 

0.260 inches at 3: 00 o'clock

**Individual Section Quantity:** 

2

**Nonturn Device Type:** 

Pin at 3: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

Pole Quantity:

1 each section front

**Throw Quantity:** 

4 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

**Rotor Through Connection Quantity:** 

1 each section

**Switch Actuator Indexing Position Quantity:** 

4 single actuator

**Shaft Type:** 

Round, flatted single actuator

## **NSN 5930-01-265-7966**Rotary Switch - Page 2 of 2



| Terminal Type:  |
|---|
| Tab, solder lug   |
| Contact Switching Action:   |
| Breaks before makes each section rear   |
| Switch Actuator Positioning Increment:  |
| 45.0 degrees single actuator  |
| Switch Actuator Stop Device Type:   |
| Fixed stop single actuator  |
| Contact Load Current Rating:  |
| 500.0 milliamperes resistive load dc at sea level and 250.0 milliamperes inductive load dc at sea level                                     |
| Style Designator:   |
| Tap, circular, bushing mount  |
| Test Data Document:   |
| 81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                           |
| Thread Series Designator:   |
| Unef single mounting facility   |
| Specification Data:   |
| 81349-mil-s-3786/13 government specification  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A052b0  |