

View Online at <https://aerobasegroup.com/nsn/5930-01-265-7969>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.292 inches single mounting facility and 0.332 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof and moisture resistant

**Overall Length:**

1.965 inches

**First Flat Length:**

0.230 inches single actuator and 0.270 inches single actuator

**Flat Height:**

0.084 inches single actuator and 0.104 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.355 inches single actuator and 0.395 inches single actuator

**Overall Diameter:**

Between 0.670 inches and 0.800 inches

**Nonturn Device Radius:**

0.260 inches at 3:00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Pin at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

7 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level and 250.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef single mounting facility

**Specification Data:**

81349-mil-s-3786/13 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0