NSN 5930-01-265-7992

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-265-7992
Overall Length:
10.188 inches
Overall Height:
6.750 inches
Overall Width:
6.750 inches
Unthreaded Mounting Hole Diameter:
0.525 inches single mounting facility
Individual Section Quantity:
4
Longest Horizontal Distance Between Mounting Centers:
5.625 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
5.625 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Terminal Type:
Threaded stud
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
200.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Test Data Document:
81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-s-15291/11 government specification
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5930-01-265-7992

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0