NSN 5930-01-265-8000

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-265-8000

9 F
Overall Length:
12.060 inches
Overall Height:
2.810 inches
Overall Width:
2.810 inches
First Flat Length:
0.380 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
0.380 inches single actuator
Unthreaded Mounting Hole Diameter:
0.213 inches single mounting facility
Individual Section Quantity:
25
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section periphery
Throw Quantity:
8 each section periphery
Mounting Facility Circle Radius:
1.625 inches single mounting facility
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Contact Voltage Rating In Volts:
125.0 ac at sea level
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
8 single actuator
Shaft Type:
Round, nonparallel flatted single actuator
Terminal Type:
Screw
Contact Switching Action:
Breaks before makes each section periphery
Switch Actuator Positioning Increment:
45.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes inductive load ac at sea level

NSN 5930-01-265-8000

Rotary Switch - Page 2 of 2

A052b0



Precious Material And Location:
Contact and rotor blade surfaces silver
Precious Material:
Silver
Style Designator:
Tap, circuit selector
Test Data Document:
81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-s-21604/6 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: