

View Online at <https://aerobasegroup.com/nsn/5930-01-265-8004>

Overall Length:

4.937 inches

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

0.468 inches single actuator

Overall Diameter:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.312 inches single mounting facility

Distance Between Mounting Facility Centers:

3.812 inches single mounting facility

Individual Section Quantity:

8

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Base single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round w/through hole single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-15291/7 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0