

View Online at <https://aerobasegroup.com/nsn/5930-01-265-8011>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

5.120 inches

**Overall Diameter:**

5.690 inches

**Unthreaded Mounting Hole Diameter:**

0.375 inches single mounting facility

**Individual Section Quantity:**

3

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Facility Circle Radius:**

2.810 inches single mounting facility

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Mounting Facility Pattern:**

Three position circular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Rectangular/square, threaded hole single actuator

**Square Shaft Size:**

0.252 inches single actuator

**Terminal Type:**

Screw

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Special Features:**

Nshaft length: any acceptable was the response reflected from the old data before crossed to new mracs and fiig; body length: 3.000 in. No.; switch actuator qty: 1; material enclosure type: metallic; frequency in hertz: 60.0

**Style Designator:**

Circular wafer, panel mount

**Test Data Document:**

81349-mil-s-15743 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-s-15743/16 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0