

View Online at <https://aerobasegroup.com/nsn/5930-01-265-8011>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.120 inches

Overall Diameter:

5.690 inches

Unthreaded Mounting Hole Diameter:

0.375 inches single mounting facility

Individual Section Quantity:

3

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

2.810 inches single mounting facility

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.252 inches single actuator

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Special Features:

Nshaft length: any acceptable was the response reflected from the old data before crossed to new mracs and fiig; body length: 3.000 in. No.; switch actuator qty: 1; material enclosure type: metallic; frequency in hertz: 60.0

Style Designator:

Circular wafer, panel mount

Test Data Document:

81349-mil-s-15743 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-15743/16 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0