

View Online at <https://aerobasegroup.com/nsn/5930-01-266-0619>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Bushing Length:**

0.500 inches

**Body Length:**

1.172 inches

**Body Width:**

0.625 inches

**Body Height:**

0.609 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.234 inches

**Actuator Height:**

0.688 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position locked in

**Maximum Voltage Rating In Volts:**

250.0 ac and 12.0 dc

**End Application:**

General application electronics (gen-ap-e)

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

35.000 amperes inductive dc and 25.000 amperes lamp dc and 10.000 amperes resistive ac

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

2 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0