

View Online at <https://aerobasegroup.com/nsn/5930-01-266-1136>

Thread Class:

2a single mounting facility

Thread Length:

0.265 inches single mounting facility

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

1.050 inches

First Flat Length:

0.265 inches single actuator

Flat Height:

0.104 inches single actuator

Shaft Diameter:

0.126 inches single actuator

Shaft Length:

0.390 inches single actuator

Overall Diameter:

0.515 inches

Individual Section Quantity:

1

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level and 75.0 milliamperes inductive load dc at sea level

Special Features:

Panel and shaft seal

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0