NSN 5930-01-266-1875

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-266-1875

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

1.459 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.094 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

0.545 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

End Application:

Radio set an/prc-114

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

5 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Pull to turn

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug and turret

NSN 5930-01-266-1875

Rotary Switch - Page 2 of 2

Fiig: A052b0



Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
36.0 degrees single actuator
Contact Load Current Rating:
200.0 milliamperes resistive load dc at sea level
Special Features:
Rear terminal area shall be sealed
Precious Material And Location:
Terminal surfaces silver and terminal and contact surfaces gold
Precious Material:
Silver and gold
Style Designator:
Snap or line
Thread Series Designator:
Unf single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No