NSN 5930-01-266-1877

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-266-1877

Thread Class:
2b single mounting facility

Overall Length:

7.810 inches

Overall Height:

4.000 inches

Overall Width:

4.000 inches

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

2.300 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.300 inches single mounting facility

Operating Tempurature Range:

-25.0/+125.0 degrees fahrenheit

End Application:

6115-00-450-5881 generator set, diesel engine

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

240.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

20.0 amperes resistive load lowest ac voltage rating at sea level and 20.0 amperes inductive load lowest ac voltage rating at sea level

Special Features:

Legend reads local remote

NSN 5930-01-266-1877

Rotary Switch - Page 2 of 2



Precious Material And Location:
Terminal surfaces silver
Precious Material:
Silver
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0