

View Online at <https://aerobasegroup.com/nsn/5930-01-266-4098>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

6.060 inches

Overall Height:

6.000 inches

Overall Width:

7.500 inches

Unthreaded Mounting Hole Diameter:

0.530 inches single mounting facility

Distance Between Mounting Facility Centers:

6.380 inches single mounting facility

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

6.0 amperes inductive load lowest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0