Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-266-4098

Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
6.060 inches
Overall Height:
6.000 inches
Overall Width:
7.500 inches
Unthreaded Mounting Hole Diameter:
0.530 inches single mounting facility
Distance Between Mounting Facility Centers:
6.380 inches single mounting facility
Individual Section Quantity:
1
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
440.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Two position in-line single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Screw
Contact Switching Action:
Breaks before makes single section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
6.0 amperes inductive load lowest ac voltage rating at sea level
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:

NSN 5930-01-266-4098

Rotary Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A052b0

