## NSN 5930-01-266-6002

**Hazardous Locations/environmental Protection:** 

Sensitive Switch - Page 1 of 2

**Body Style:**Hole mounted

Dustproof

Overall Length: 1.673 inches

1.000 inches



View Online at https://aerobasegroup.com/nsn/5930-01-266-6002

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

Overall Height:
1.579 inches
Overall Width:
1.380 inches
Body Length:
1.940 inches
Body Width:
1.380 inches
Unthreaded Mounting Hole Diameter:
0.139 inches
Actuator Length:
1.203 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.219 inches
Actuator Roller Diameter:
0.370 inches
Actuator Roller Width:
0.150 inches
Maximum Voltage Rating In Volts:
480.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
14.0 ounces
Actuator Movement:
Between 0.030 pretravel inches and 0.040 overtravel inches and 0.156 differential inches

## NSN 5930-01-266-6002

Sensitive Switch - Page 2 of 2

**Fiig:** A053a0



Contact Load Current Rating At Maximum Rated Voltage:
25.000 amperes resistive ac
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No