

View Online at <https://aerobasegroup.com/nsn/5930-01-266-7865>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.359 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Length:

0.200 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.570 inches

Actuator Roller Diameter:

0.188 inches

Actuator Roller Width:

0.109 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.5 ounces

Switch Actuating Force:

6.0 ounces

Actuator Movement:

0.094 pretravel inches and 0.047 overtravel inches and 0.031 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0