

View Online at <https://aerobasegroup.com/nsn/5930-01-267-0954>

Thread Class:

2b 1st mounting facility

Unthreaded Mounting Hole Diameter:

0.312 inches 2nd mounting facility

Distance Between Mounting Facility Centers:

3.812 inches 2nd mounting facility

Individual Section Quantity:

15

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.609 inches 1st mounting facility

Mounting Method:

Bracket 2nd mounting facility and unthreaded hole 2nd mounting facility

Features Provided:

Actuator knob and dummy section

Thready Qty Per Inch (tpi):

20 1st mounting facility

Thread Size:

0.250 inches 1st mounting facility

Contact Voltage Rating In Volts:

120.0 dc at sea level

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0