NSN 5930-01-267-5800

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-267-5800

Body Style:
Hole mounted
Overall Length:
0.510 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.188 inches
Overall Width:
0.200 inches
Body Length:
0.510 inches
Body Width:
0.200 inches
Body Height:
0.350 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.063 inches
Actuator Height:
0.050 inches
Actuator Free Position Height:
0.340 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
5.0 ounces
Actuator Movement:
Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc
Terminal Type And Quantity:

2 wire lead

NSN 5930-01-267-5800

Sensitive Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0