## NSN 5930-01-268-2891

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-268-2891

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.940 inches
Body Width:
0.690 inches
Unthreaded Mounting Hole Diameter:
0.170 inches
Actuator Style:
Round
Actuator Diameter:
0.280 inches
Maximum Voltage Rating In Volts:
480.0 ac and 125.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement.
1 pole, double throw, both positions maintained single switch unit
1 pole, double throw, both positions maintained single switch unit
1 pole, double throw, both positions maintained single switch unit  Switch Release Force:
1 pole, double throw, both positions maintained single switch unit  Switch Release Force:  4.0 ounces
1 pole, double throw, both positions maintained single switch unit  Switch Release Force:  4.0 ounces  Switch Actuating Force:
1 pole, double throw, both positions maintained single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force:  Between 8.8 ounces and 12.5 ounces
1 pole, double throw, both positions maintained single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: Between 8.8 ounces and 12.5 ounces  Actuator Movement:
1 pole, double throw, both positions maintained single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: Between 8.8 ounces and 12.5 ounces  Actuator Movement:  Between 0.016 pretravel inches and 0.063 overtravel inches and 0.002 differential inches
1 pole, double throw, both positions maintained single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: Between 8.8 ounces and 12.5 ounces  Actuator Movement: Between 0.016 pretravel inches and 0.063 overtravel inches and 0.002 differential inches  Contact Load Current Rating At Maximum Rated Voltage:
1 pole, double throw, both positions maintained single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: Between 8.8 ounces and 12.5 ounces  Actuator Movement: Between 0.016 pretravel inches and 0.063 overtravel inches and 0.002 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 500.000 milliamperes resistive dc and 15.000 amperes resistive ac
1 pole, double throw, both positions maintained single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: Between 8.8 ounces and 12.5 ounces  Actuator Movement: Between 0.016 pretravel inches and 0.063 overtravel inches and 0.002 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 500.000 milliamperes resistive dc and 15.000 amperes resistive ac  Terminal Type And Quantity:
1 pole, double throw, both positions maintained single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: Between 8.8 ounces and 12.5 ounces  Actuator Movement: Between 0.016 pretravel inches and 0.063 overtravel inches and 0.002 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 500.000 milliamperes resistive dc and 15.000 amperes resistive ac  Terminal Type And Quantity: 3 screw
1 pole, double throw, both positions maintained single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: Between 8.8 ounces and 12.5 ounces  Actuator Movement: Between 0.016 pretravel inches and 0.063 overtravel inches and 0.002 differential inches  Contact Load Current Rating At Maximum Rated Voltage:  500.000 milliamperes resistive dc and 15.000 amperes resistive ac  Terminal Type And Quantity: 3 screw  Shelf Life:
1 pole, double throw, both positions maintained single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: Between 8.8 ounces and 12.5 ounces  Actuator Movement: Between 0.016 pretravel inches and 0.063 overtravel inches and 0.002 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 500.000 milliamperes resistive dc and 15.000 amperes resistive ac  Terminal Type And Quantity: 3 screw  Shelf Life: N/a
1 pole, double throw, both positions maintained single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: Between 8.8 ounces and 12.5 ounces  Actuator Movement: Between 0.016 pretravel inches and 0.063 overtravel inches and 0.002 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 500.000 milliamperes resistive dc and 15.000 amperes resistive ac  Terminal Type And Quantity: 3 screw  Shelf Life: N/a
1 pole, double throw, both positions maintained single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: Between 8.8 ounces and 12.5 ounces  Actuator Movement: Between 0.016 pretravel inches and 0.063 overtravel inches and 0.002 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 500.000 milliamperes resistive dc and 15.000 amperes resistive ac  Terminal Type And Quantity: 3 screw  Shelf Life: N/a  Unit Of Measure:
1 pole, double throw, both positions maintained single switch unit  Switch Release Force: 4.0 ounces  Switch Actuating Force: Between 8.8 ounces and 12.5 ounces  Actuator Movement: Between 0.016 pretravel inches and 0.063 overtravel inches and 0.002 differential inches  Contact Load Current Rating At Maximum Rated Voltage: 500.000 milliamperes resistive dc and 15.000 amperes resistive ac  Terminal Type And Quantity: 3 screw  Shelf Life: N/a  Unit Of Measure:  Demilitarization: