NSN 5930-01-268-5191

Push Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-01-268-5191

Panel mounted
Hazardous Locations/environmental Protection:
Driptight and dustproof and moisture resistant
Overall Length:
2.355 inches
Overall Height:
0.960 inches
Overall Width:
0.960 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.275 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator and black single actuator
Illuminated Actuator Color:
Red single actuator and yellow single actuator
Actuator Inscription:
Js fcc tscc single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator yellow lower half of actuator red
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Mounting Surface To Terminal End Distance:
Between 1.720 inches and 1.880 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:

Actuator seal and horizontal split lens

NSN 5930-01-268-5191

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 tab, solder lug and 12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0