

View Online at <https://aerobasegroup.com/nsn/5930-01-268-5200>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Driptight and dustproof and moisture resistant

Overall Length:

2.355 inches

Overall Height:

0.960 inches

Overall Width:

0.960 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Case Material:

Metal

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.275 inches

Actuator Width:

0.620 inches

Actuator Color:

Black single actuator and black single actuator

Illuminated Actuator Color:

Red single actuator and yellow single actuator

Actuator Inscription:

Capt capt single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator yellow lower half of actuator red

Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

Mounting Surface To Terminal End Distance:

Between 1.720 inches and 1.880 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and horizontal split lens

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 tab, solder lug and 12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0